



Precise 100 AX



- **Fingerprint reader for PC environments**
- **Increased security—no passwords or PINs to remember**
- **Reduced costs for password administration**
- **Simplified logon procedure**
- **Compliant with the BioAPI and HA-API standards**



Precise 100 AX is a fingerprint reader for PC and network access control. Fingerprints replace passwords and make the logon procedure quick and easy for the user. By using Precise 100 AX, it is possible to achieve an increased level of security in line with existing IT policies while saving time and money on password administration issues.

Being one of the most compact biometric devices on the market, the Precise 100 AX attracts a wide range of users. Its ergonomic design makes fingerprint placement problem-free and usage successful. It plug-and-play installs in the following Windows environments: Windows XP, Windows 2000, Windows 98 and Windows Me.

Precise 100 AX is compatible with the BioAPI and HA-API-compliant Precise BioMatch™ Standard software. With Precise BioMatch™ Standard all fingerprint information is stored and matched on a server or on a PC. Together with a stand-alone smart card reader, Precise 100 AX can also be used with the Precise Match-on-Card™ software Precise BioMatch™ Pro.

SPECIFICATIONS

030508

Precise 100 AX

GENERIC FEATURES

- Fingerprint reader for PC environments
- Increased security—no passwords or PINs to remember
- Reduced costs for password administration
- Simplified logon procedure
- Compliant with the BioAPI and HA-API standards

TECHNICAL SPECIFICATION

General

- Size: 67 x 50 x 15 mm / 2.6 x 2.0 x 0.6 inches (L x W x H)
- Power consumption: standby: 0.5 mA
 normal idle: 80 mA
 max: 100 mA
- Operating temperature range: 0-50° C / +32-120° F
- USB connection
- FCC (Part 15 Class B) and CE certified
- UL 1950 (Safety of Information Technology Equipment, Including Electrical Business Equipment) certified
- ISO9000/1 and ISO14001 production certified
- Drivers: Windows® 98 SE
 Windows® Me
 Windows® 2000
 Windows® XP

Biometric Reader

- Silicon fingerprint sensor—AuthenTec AES4000
- BioAPI compatible
- Capturing of up to 3 fingerprint images/second

SYSTEM REQUIREMENTS

- Windows® XP, Windows® 2000, Windows® 98 (Service Pack 1) or Windows® Me
- USB Port



All specifications are subjects to change without notice

