


# CIRCULAR POLARISED UHF ANTENNA

## SlimLine - A4030C

### ABOUT TIMES-7

Pushing the boundaries of RFID technology worldwide Times-7 are leaders in RFID antenna design and manufacture. Our patented award winning UHF antennas meet the needs of virtually any industry application; providing customers with fast accurate tracking of products, assets & people; empowering organisations to transform processes & reduce costs.

Our SlimLine range of antennas are unique in the RFID industry; offering high levels of performance & durability in an aesthetically superior form. Proven in a diverse & growing range of markets, applications include: retail & customer interaction, conference & people tracking, race timing, baggage handling, and logistic & supply chain asset management.



*The SlimLine A4030C*

Up to 6 m / 19.5 ft. read range

Just 12mm / 0.5 in. thick

Versatile & compact with superb aesthetics

Seamless installation using rear connector

Part of the SlimLine range of multi-purpose antennas, the A4030C is a rugged high performance circular polarised UHF antenna suitable for a wide range of RFID deployments. With a read range of up to 6m / 19.5ft., and dimensions of only 280 mm / 11 in. square, the A4030C is an extremely versatile and compact antenna. A rear connector provides for ease of seamless installation with no visible cable.

## Specifications


### Physical / Environmental Specifications

Dimensions (LxWxD):	280 mm x 280 mm x 12 mm 11 in. x 11 in. x 0.5 in.
Weight:	0.75kg / 1.6 lbs.
Radome Material:	Fire retardant Kydex
Environmental Rating:	IP65
Operating / Storage Temperature:	-20° to +55°C / -30° to +65°C -4° to +131°F / -22° to +149°F
Connector type / position:	SMA female / Rear connector
Cable:	2m SMA to RPTNC (included)


### Electrical Specifications

Frequency Range:	864 – 869 MHz / 902 – 928 MHz
Polarisation:	Circular
Far-field Gain:	6.5dBic
Far-field 3dB beamwidth:	60° in both planes
Typical VSWR across frequency range:	< 1.4:1
Front to back ratio:	26dB
Axial Ratio:	<2dB at boresight
Nominal Impedance:	50 Ω
Anti-static protection:	Yes
Maximum Input Power:	6 W

*E-field elevation & Azimuth Patterns*



Vertical




Horizontal

**Ordering Information (please quote both product code & part no.)**

Product Code	Band	Part No.
A4030C	ETSI 864-869 MHz	71269
A4030C	FCC 902-928 MHz	71270
Cable 4m, SMA to RPTNC		71437
Cable 8m, SMA to RPTNC		71438

## Applications

- Inventory Management
- Logistics & Supply Chain
- Healthcare (asset & people tracking)
- Retail / POS self service



### OUR GLOBAL NETWORK

Constantly increasing market reach and influence in the global RFID industry, Times-7's international support spans The Americas, Europe, and Asia Pacific regions through our distributor, authorized reseller and integrated solutions provider network.

TransTech Systems, Inc.  
12142 NE Sky Lane  
Suite 130  
Aurora, OR 97002

Ph: 888-843-3643  
Fax: 503-682-0166

[sales@ttsys.com](mailto:sales@ttsys.com)  
[www.ttsys.com](http://www.ttsys.com)