

ABOUT TIMES-7

Pushing the boundaries of RFID technology worldwide Times-7 are leaders in RFID antenna design and manufacture. Our patented award winning UHF antennas meet the needs of virtually any industry application; providing customers with fast accurate tracking of products, assets & people; empowering organisations to transform processes & reduce costs.

Our SlimLine range of antennas are unique in the RFID industry; offering high levels of performance & durability in an aesthetically superior form. Proven in a diverse & growing range of markets, applications include: retail & customer interaction, conference & people tracking, race timing, baggage handling, and logistic & supply chain asset management.



The SlimLine A6034S

Up to 9m / 29 ft. read range

Just 12 mm / 0.5 in. thick

High performance & rugged design

Suitable for indoor/outdoor use
& industrial applications

Part of the SlimLine range of multi-purpose antennas, the A6034S is an ultra-low profile high performance circular polarised flat panel antenna. With a read range of up to 9m / 29ft. and utilising a narrow even beam, the A6034S provides for a highly accurate read zone. The rugged design of the A6034S makes it suitable for a range of indoor / outdoor RFID deployments, including industrial applications.

Specifications


Physical / Environmental Specifications

Dimensions (LxWxD):	394 mm x 394 mm x 12 mm 15.5 in. x 15.5 in. x 0.5 in.
Weight:	1.75kg / 3.8 lbs.
Radome Material:	Fire retardant Kydex
Environmental Rating:	IP65
Operating / Storage Temperature:	-20° to +55°C / -30° to +65°C -4° to +131°F / -22° to +149°F
Mounting:	Integrated mounting holes / no accessory req.
Connector type / position:	SMA female side fly lead (300mm / 1ft)
Cable:	2m SMA to RPTNC (included)


Electrical Specifications

Frequency Range:	864 – 869 MHz / 902 – 928 MHz
Polarisation:	Circular
Far-field Gain:	9dBic
Far-field 3dB beamwidth:	50° in both planes
Typical VSWR across frequency range:	< 1.4:1
Front to back ratio:	13dB
Axial Ratio:	<2dB at boresight
Nominal Impedance:	50 Ω
Anti-static protection:	Yes
Maximum Input Power:	6 W

E-field elevation & Azimuth Patterns



Vertical




Horizontal

Ordering Information (please quote both product code & part no.)

Product Code	Band	Part No.
A6034S	ETSI 864-869 MHz	71002
A6034S	FCC 902-928 MHz	71003
Cable 4m, SMA to RPTNC		71437
Cable 8m, SMA to RPTNC		71438

Applications

- High performance RFID applications where long / highly accurate read zones are required
- Space constrained / Customer facing environments
- All-weather rugged design suitable for industrial applications



OUR GLOBAL NETWORK

Constantly increasing market reach and influence in the global RFID industry, Times-7's international support spans The Americas, Europe, and Asia Pacific regions through our distributor, authorized reseller and integrated solutions provider network.

TransTech Systems, Inc.
12142 NE Sky Lane
Suite 130
Aurora, OR 97002

Ph: 888-843-3643
Fax: 503-682-0166

sales@ttsys.com
www.ttsys.com