

## MERCURY6

### 4-Port Enterprise UHF RFID Reader



The Mercury6 (M6) is a low profile, high-performance 4-port RFID reader designed for both indoor and outdoor applications. Driven by ThingMagic's powerful Mercury6e UHF RFID reader module, the M6 Power over Ethernet (PoE) and WiFi options allow for flexible, low cost, installations. With full support for ThingMagic's enterprise-class MercuryOS software, M6 is compatible with both corporate IT infrastructures and sheltered outdoor environments.

Tag / Transponder Protocols	
RFID Protocol Support	EPCglobal Gen2 (ISO 18000-6C) with DRM ISO 18000-6B (optional) IP-X (EM 412x) (optional)
UHF RFID Antenna Interface	
Interface	Four RP-TNC connectors
RF Power Output	Separate read and write levels, adjustable from 5 dBm to 31.5 dBm* (1.4W) with +/-0.5 dBm accuracy above +15 dBm
Frequency	902-928 MHz (FCC; NA, SA) 865.6-867.6 MHz (ETSI; EU) 865-867 MHz (MCIT; India)
Data/Control/Wireless Interfaces	
Connectors	RJ45 (10/100 Base-T Ethernet) USB Type B (console port) USB Type A (accessory port) HD15 (GPIO interface) 5.54 mm sealed connector (DC power) Reverse polarity SMA jack (optional WiFi antenna)
Wireless	Internal 802.11 b/g (optional) WEP 40-bit and 104-bit keys; WPA & WPA2 with TKIP and AES algorithms with pre-shared keys or EAP-TLS USB type A interface permits future support for external wireless technologies.
Indicators, switches, and GPIOs	1 two-color LED status indicator; Reset switch; Isolated GPIOs; 4 Inputs & 4 Outputs plus +5 VDC and grounded references
Physical	
Dimensions	19 cm L x 17.8 cm W x 3.4 cm H (7.5 in L x 7.0 in W x 1.3 in H)
Weight	2 lbs (0.9 kg)
Regulatory & Safety	
Regulatory	FCC 47 CFR Ch.1 Part 15 Industrie Canada RSS-21 0 ETSI EN 302 208 V1.2.1
Other	RoHS compliant per EU directive 2002/95/EC, UL Listed (Pending)

Power	
Power Over Ethernet	Power over Ethernet 802.3af in both modes A and B (Supports 100m cable).
External DC Power	10- 30 VDC supply voltage. Maximum DC power: 15 W
Environment	
Operating Temp.	-20C to +50C
Storage Temp.	-40C to +85C
Dust and water immunity	IP52
Humidity	5% to 95%, non-condensing
Architecture	
Operating System	Linux kernel version 2.6
Performance	
Max Tag Read Rate	Over 400 tags/second
Max Tag Read Distance	Over 30 feet (9 m) with 6 dBi antenna (36 dBm EIRP)
Max EPC ID Length	Up to 496 bits
MercuryOS Features	
Networking	Cisco-certified DHCP & DNS-based configuration and firmware management, TCP/IP networking stack
Security	SSL/SSH-based security
Web-Based Control	Configuration and Monitoring from a web browser; HTTP/HTTPS



TEL: 1-888-843-3643  
 EMAIL: [sales@ttsys.com](mailto:sales@ttsys.com)  
[www.ttsys.com](http://www.ttsys.com)



## Develop

Create RFID-enabled solutions  
using industry-standard tools

## Deploy

Enable rapid deployment and reliable  
operation of RFID solutions within a wide  
variety of new and existing environments

## Optimize

Maximize productivity, improve ROI,  
and lower operating costs



For more information, visit [www.ttsys.com](http://www.ttsys.com)

To purchase ThingMagic products, please email  
[sales@ttsys.com](mailto:sales@ttsys.com) or call 888-843-3643

TransTech Systems Inc  
12142 NE Sky Lane Suite 130  
Aurora, OR 97002

©2010 ThingMagic – a division of Trimble Navigation Limited.  
ThingMagic and The Engine in RFID are registered trademarks  
of Trimble Navigation Limited. Other marks may be protected  
by their respective owners. All Rights Reserved.