

LINEAR POLARISED GROUND ANTENNA SlimLine - A5531

ABOUT TIMES-7

Pushing the boundaries of RFID technology worldwide Times-7 are leaders in RFID antenna design and manufacture. Our patented award winning UHF antennas meet the needs of virtually any industry application; providing customers with fast accurate tracking of products, assets & people; empowering organisations to transform processes & reduce costs.

Our SlimLine range of antennas are unique in the RFID industry; offering high levels of performance & durability in an aesthetically superior form.

Proven in a diverse & growing range of markets, applications include: retail & customer interaction, conference & people tracking, race timing, baggage handling, and logistic & supply chain asset management.



Part of the Times-7 unique and exclusive range of ground antennas, the A5531 is a high performance ground antenna optimised for applications involving moving products, assets and people. From conference attendee & people tracking, retail presence aware / loyalty marketing, & race timing, the A5531 is ideal for situations where traditional side antennas are unsuitable or non-optimised for the application.

At just 10 mm / 0.4 in. thick, the durable, high performance A5531 is uniquely capable of lying flat on the ground and spans 1.2m / 4ft, and can withstand payloads of over 200 kg (440 lbs.).

Specifications

Physical / Environmental Specifications

- Hydrom / = Horn driller dp dd Horn da dd Horn	
Dimensions (LxWxD):	1200 mm x 195 mm x 10 mm
	48 in. x 7.7 in. x 0.4 in.
Weight:	2.7 kg / 5.9 lbs.
Radome Material:	Fire retardant Kydex
Environmental Rating:	IP53
Operating / Storage Temperature:	0° to +50°C / -30° to +60°C
	32° to +122°F / -22° to +140°F
Connector type / position:	SMA female mid-point fly lead (300 mm / 1 ft.)
Cable:	2m SMA to RPTNC (included)

Electrical Specifications

Frequency Range:	864 - 869 MHz / 902 - 928 MHz	
Polarisation:	Linear	
Far-field Gain:	10dBi	
Far-field 3dB beamwidth:	70° in XZ, 25° in YZ	
Typical VSWR across frequency range:	< 1.8:1	
Front to back ratio:	20dB	
Nominal Impedance:	50 Ω	
Anti-static protection:	Yes	
Maximum Input Power:	6 W	









LINEAR POLARISED GROUND ANTENNA SlimLine - A5531

E-field elevation & Azimuth Patterns





XZ-plane

YZ-plane

Ordering Information (please quote both product code & part no.)

Product Code	Band	Part No.
A5531	ETSI 865-868 MHz	71103
A5531	FCC 902-928 MHz	71100
Cable 4m, SMA to RPTNC		71437
Cable 8m, SMA to RPTNC		71438

Applications

- Event & Race Timing
- Conference Attendee / People Tracking
- Industrial Asset Tracking







OUR GLOBAL NETWORK

Constantly increasing market reach and influence in the global RFID industry, Times-7's international support spans The Americas, Europe, and Asia Pacific regions through our distributor, authorized reseller and integrated solutions provider network.

TransTech Systems, Inc. 12142 NE Sky Lane Suite 130 Aurora, OR 97002

Ph: 888-843-3643 Fax: 503-682-0166

sales@ttsys.com www.ttsys.com



