



ALH-90xx

Compact/Connected Handheld RFID Reader

The Alien Technology® enterprise-level ALH-90xx family of “connected” handheld readers enables users to deploy manageable, robust, best-in-class EPC Gen 2 RFID solutions for supply chain, manufacturing, and asset management applications.

FEATURES

- Rugged yet compact and lightweight for ease of use
- Ergonomic design provides superior user comfort
- “Connected” via the full set of wireless networking
- IP65 sealing for dust and water resistance
- Choose between standard or high-end model to accommodate your needs
- Prolonged usage capabilities provided by a 3,000 mAh lithium polymer main battery pack
- Windows Mobile 6.5 and Windows CE 5.0 available

Benefit	Enabled By:	What does this mean to me?
Ease of Use	<ul style="list-style-type: none"> • Simple intuitive hardware & software • Simple interfacing to corporate networks 	<ul style="list-style-type: none"> • Easy to set up and deploy • Less maintenance and overhead • Minimizes network infrastructure
Rugged, yet light, compact, and ergonomic	<ul style="list-style-type: none"> • Rugged IP65 rated design • Light-weight and smaller than comparable solutions 	<ul style="list-style-type: none"> • Low risk enterprise solution • Easier to handle than other solutions
Full featured & expandable	<ul style="list-style-type: none"> • Enterprise class Microsoft O/S (Windows Mobile 6.5 or Windows CE 5.0) • 1D or 2D bar-code support • Camera • WiFi, Cellular, GPS, and Bluetooth • Slots for memory, SIM's, 2nd battery 	<ul style="list-style-type: none"> • Single solution for all handheld needs • Grows with your needs • Wireless simplicity



Compact/Connected Enterprise Handheld

This feature-rich reader delivers exceptional performance with best-in-class receive sensitivity, enhanced interference rejection, compact ergonomic footprint, delivering high read rates for demanding applications in an easy-to-integrate, easy-to-manage package.

Fully Loaded

The ALH-9000 (Win CE) and ALH-9010 (Windows Mobile) come well featured including basic bar code (1D) capability and WiFi connectivity to your corporate network. The 3.5" touch sensitive color display clearly conveys reader status and enables interaction with standard or customized applications. A memory expansion slot is standard for flexibility for additional local storage.





Compact/Connected Handheld RFID Reader

High Performance, Easy to Use, Easy to Manage, Easy to Deploy

Standard accessories include:

- Cradle with ethernet and USB
- Gun handle
- Sync cable
- Power adapter for US or Europe
- Stylus pen
- Hand strap
- Protective screen film

The step-up units, the ALH-9001 (Win CE) and ALH-9011 (Windows Mobile) adds a number of features including 2D bar code reader, camera (with flash), Bluetooth, GPS (for location aware applications), and HSDPA 3G cellular connectivity for use beyond corporate WiFi areas.

All units are offered in regional frequency options including "US", "European" and others.



Baseline Specification	ALH-9010 (Windows Mobile) ALH-9000 (Windows CE)
RFID Reader	RFID UHF reader
Scanner	1-D bar code
Networking	Wireless WLAN 802.11b/g
Communications	USB host & client
Operating System	ALH-900x: Windows CE NET 5.0 ALH-901x: Windows Mobile 6.5
Display	3.5" color QVGA touch screen
CPU	Marvel PXA320, 820MHz
Memory	256MB RAM / 256MB ROM
Battery	3,000mAh lithium polymer
Expansion Slot	1 Micro SD slot, 1 SIM slot
Weight without gun battery	1.22 lbs / 0.55Kg
Weight with gun battery	1.42 lbs / 0.65Kg
Dimensions without gun handle	6.25" (L) x 3.1" (W) x 4.6" (H) 15.9cm (L) x 7.9cm (W) x 11.7cm (H)
Dimensions with gun handle	6.25" x 3.1" (W) x 5.3" (H) 15.9cm (L) x 7.9cm (W) x 13.5cm (H)

Step-Up Features (Added to Baseline Specification)	ALH-9011 (Windows Mobile) ALH-9001 (Windows CE)
Scanner	2-D bar code scanner
Camera	3 mega-pixel fixed focus with flash
Body Network	Wireless Bluetooth v2.0, Class II (SPP)
Cellular Network	Wireless HSDPA
Location Services	GPS
Battery	Additional 4,400mAh high capacity battery

Physical Characteristics	
Ingress Protection	IP65
Drop	1.5 Meters (5 feet) - 6 axis (1 foot greater than MIL-STD-810 G)
ESD	Contact \pm 4KV / \pm Air 8KV
Humidity	0-95% at 40°C / 104°F
Operating Temp	-10°C to 50°C / 14°F to 122°F



Compact/Connected Handheld RFID Reader

High Performance, Easy to Use, Easy to Manage, Easy to Deploy

Included Accessories

Gun Handle

Cradle with Ethernet

Sync Cable

Power Adapter US or EU

Stylus Pen

Hand Strap

Protective Film

Additional Accessories

Ordering Information

Description

ALX-503 4,400mAh high capacity battery for gun handle option

ALX-504 Spare 3,000mAh standard lithium polymer battery

ALX-505 Leather case

ALX-506 Vehicle charger cable

Ordering Information

Operating System

Baseline or Step-Up

Country Code

NOTE: This list is being added to daily. Please contact your Alien Representative for a full list

ALH-90

x

x

-

xxx

0 = Windows CE Net 5.0

0 = Base

(blank) = North America

1 = Windows Mobile 6.5

1 = Step-Up

EMA = Europe

CHN = China

Examples:

ALH-9011-EMA - Windows Mobile unit, step-up features for Europe

ALH-9000 - Windows CE, base unit for North America



TransTech Systems, Inc. 12142 NE Sky Lane Suite 130 Aurora, OR 97002

Ph: 888-843-3643 Fax: 503-682-0166 sales@ttsys.com www.ttsys.com

Copyright © 2012 Alien Technology Corporation. All rights reserved.

Alien, Alien Technology, the Alien Technology logo, FSA, Higgs, Dynamic Authentication, Quick-Write, Squiggle, and the Squiggle logo are trademarks or registered trademarks of Alien Technology Corporation in the U.S. and other countries.

HANDLING PRECAUTIONS Observe standard handling practices to minimize ESD.

DISCLAIMER Application recommendations are guidelines only - actual results may vary and should be confirmed. This is a general purpose product not designed or intended for any specific application.

This product is covered by one or more of the following U.S. patents: 7716208, 7716160, 7688206, 7671720, 7659822, 7619531, 7615479, 7598867, 7580378, 7576656, 7562083, 7561221, 7559486, 7559131, 7554451, 7411503, 7385284, 7377445, 7364084, 7353598, 7342490, 7324061, 7321159, 7301458, 7295114, 7288432, 7265675, 7262686, 7215249, 7214569, 7199527, 7193504, 7173528, 7172910, 7172789, 7141176, 7113250, 7101502, 7080444, 7070851, 7068224, 7048328, 6998644, 6988667, 6985361, 6980184, 6970219, 6952157. Other patents pending.

20 September 2012