

SMART-30S is Value for Everyone!

www.idp-corp.com

Overlay •

UV Panel ●



Applications

- ID / Membership
- Access control / Security
- Healthcare
- Government
- Banking Card
- Transportation
- Retail
- Gift / Promotion / Loyalty

Features

- Color & Mono Printing
- Transparent Card with Magnetic Stripe
- Full Encoding Support (Magnetic, Contact, Contactless)
- Removable Stacker
- Compact Size



SMART-30S Specifications

SMART-30S (Single Side Card Printer)

Printing

Dye-Sublimation **Print Type** Print Area Edge to Edge

0 300 dpi Resolution O TBD **Dual Side Printing**

Card /

Card Feeding Automatic

Card Size 0 ISO CR80 (54mm x 86mm / 2.12" x 3.38")

Card Thickness 0 0.38mm(15mil) ~ 0.76mm(30mil)

O PVC, Composite PVC, PET Card Type

Print Speed

Monochrome 5 sec. (720 cards/hour) **YMCKO** 28 sec. (128 cards/hour)

Capacity

Input Hooper 0 80 cards **0 25 cards Output Hooper**

System

O 64MB RAM Memory Control Panel LED Button

Supported Platforms O Microsoft Windows 2000/2003/XP/Vista/7,

Mac OS, Linux

Communication O USB, Ethernet (Option)

Power Supply O Free Voltage (AC 110/220V, 50~60Hz)

Power Consumption (Max) 0 48W

Temperature / Humidity 0 15~35°C / 20~80%

Dimensions

0 172 mm x 377mm x 190mm Dimension (WxLxH)

0 3.4 kg / 7.5 lbs Weight

Encoding Options

0 ISO 7811 (Track I, II, III Read / Write), Magnetic

O HiCo/LoCo, JIS II

0 ISO 7816 (ID-1) Contact Smartcard

Contactless Smartcard O MIFARE, ISO 14443 (Type A / B), (Internal & External) O ISO 15693, DESFIRE, iCLASS

O CE, FCC, KCC **Certifications**





Smart, Smarter than any other ID Card Printer

