# Prima 4



## Reverse transfer ID card printer





#### The highest print quality

The reverse-transfer Prima is ideal for producing top quality, durable cards.

The image quality of the printed card is comparable to mass produced offset litho printed cards, but with the advantage that each card can be personalized.

#### Features and options











#### The Prima is ideal for:

- Driving Licenses
- Airport Cards
- National ID
- Banking/Financial Cards
- Bureau Services

#### Free 3 year warranty and support



The Prima is supplied with a free, 3 year warranty and support including loaner service, plus life-time printhead cover\*.

(Available in the EU. North America and other selected territories)

PROFESSIONAL SERIES





# The innovative Prima 4 Reverse Transfer printing technology

The Prima 4 printer's reverse transfer printing technology delivers superb print quality and is the ideal choice for printing technology embedded cards, as well as high volume batch printing.


#### The process works like this:

The ID card image is printed from the YMCK dye film onto a clear retransfer film in a "reverse image", and is then laminated onto the card surface. The printed image is protected from scratching and fading by the clear film layer. In comparison, dye sublimation printers transfer the dyes directly onto the card surface using thermal transfer dye diffusion technology, followed by a thin acrylic varnish. Both methods use YMCK dye films, but the reverse transfer method uses an additional polyester transfer film.

#### The advantages of Reverse Transfer technology are:

- · Amazing print quality
- The ability to print cards with uneven surfaces such as smart and proximity cards
- True over-the-edge printing on the card
- The ability to print onto non-PVC cards like ABS, PET, PVH and Polycarbonate

High-capacity YMCK dye film together with the separate re-transfer film provides 1000 color prints. Both dye film and re-transfer cartridges insert easily for user convenience.





## Enhanced encoding options

The new Prima printers are optionally equipped with smart card encoders, which support the following encoding technologies:

- Philips: MIFARE \*, DESFire
- HID: iCLASS
- Legic \*
- Contact Chip





Single-sided or double-sided lamination

The inline laminator integrates exclusively with the Magicard Prima. Available in single or double-sided, it delivers an outstanding lamination result with all available options. Regardless of whether the application calls for thin holographic film, or thicker overlaminate patches, the result is always superb.

Front loading of the lamination rolls is convenient and user friendly. The inline lamination unit is user programmable. Temperature and speed settings can be adjusted via the front panel display for optimum results with varying card types including PVC, PVH, ABS, 100% PET and even Polycarbonate.

Lamination materials include thin holographic overlays and 0.5 mil and 1 mil patch laminates available in clear or custom formats.

The Magicard Prima's unique portrait orientation lamination mode allows for fast operation.

### ONLY Magicard offers you all the following valuable features:

- 3 years UltraCoverPlus warranty and support (EU, North America and selected other territories).
- · Wide range of encoding options Philips Mifare, Desfire, HID iClass, Legic and Contact Chip.
- · USB 2.0 and Ethernet as standard.

- · Inline lamination options.
- · Extensive choice of field upgrades.
- · Auto dye film detection.
- · Anti-bend card output.

Visit www.magicard.com for more information.

Models



Warranty\* 3 years UltraCoverPlus warranty and support which includes full printhead coverage and free loaner service –

North America, EU and other selected territories. Elsewhere 12 months limited warranty.

Print Speed YMCK with transfer to card: up to 100 cards per hour single-sided.

**Card Capacity** 100 card input and output hoppers.

Printhead Simple field replaceable unit.

PC interfaces USB (Ver2.0) Full-Speed (12Mbps) and Hi-Speed (480Mbps) 10BASE-T/100BASE-TX Ethernet,

both included as standard.

**Printer Drivers** Windows 2000 Professional (SP4), XP (SP2, SP3), Vista (SP1), Windows Server 2003 R2 SP2, Server 2008, 7.

Security Features Holographic laminates (Requires lamination module) and UV film options.

Cleaning Removable cleaning roller cassette.

**Dimensions** 13.5" width x 12.6" height x 13" length (343mm width x 320mm height x 330mm length).

Weight 34.1lbs (15.5kg).

**Operating Conditions** 59 to 86°F (15 to 30°C); 35% to 70% non-condensing.

Set of 1 YMCK dye film + 1 retransfer film - 1000 prints -Part No Prima 431 Dye Film

> YMCKK 750 prints (Full-color printing on one side and black on reverse side) -Part No Prima 433

YMCK-UV 750 prints (Full-color and UV panel) -Part No Prima 434 .

Retransfer Film Retransfer film 1000 prints. ( Retransfer film must be paired with dye film for printing ) - Part No Prima 436

Laminates Thin, 0.5 mil and 1 mil laminates available. Clear and holographic laminates.

Card Thickness/Stock 0.25mm to 1.0mm (10mil to 40mil) / PVC, ABS, PET, PVH, and Polycarbonate ISO Standard CR80 sized cards.

Prima 4 Uno Single-sided - Part No Prima 401

Prima 4 Duo Double-sided - Part No Prima 402

Inline Laminator Compact, single-sided or double-sided -Part No Prima 451/Prima 452

Magstripe Encoder Prima with HiCo/LoCo Magstripe encoder -Part No Prima 421

Contactless Card Encoder Contactless cards supported: Philips MIFARE \*, DESFire \*, HID: iCLASS \*, Legic \*. **Smart Card Encoder** Optional chip contact programming facility for smart cards -Part No Prima 422



Highest photo-quality images, printed right over the edge of the card. Edge to edge



Encoding Magstripe - Encoder for access control, time and attendance.

Chip Contact - Programming facility for smart cards.

Contactless - Philips MIFARE \*, DESFire \*, HID: iCLASS \*, Legic \* options available.



Prints on both sides (Prima 4 Duo). Duplex

OPTIONS

www.ttsys.com

Lamination For added durability and holograms, an inline card laminator is available.

\*Warranty subject to the observance of specific conditions of use and maintenance, as well as the use of certified 'Original Magicard' dye films.

Magicard is a trademark of Ultra Electronics Limited. Windows 2000, XP and Vista are trademarks of Microsoft

The information contained in this document reflects the current state of design and we reserve the right to change the specification without notice or obligation.

Prima44PPUSLTR0210 issue 1.05





www.ttsys.com



TransTech Systems, Inc. 12142 NE Sky Lane, Suite 130 Phone: 888.843.3643 Fax: 503-682-0166 Email: sales@ttsys.com



